



7/8" BLINDS + GLASS TILT FOR WINDOWS

PRODUCT FEATURES

- For use in single/double-hung windows and light commercial applications
- Blinds remain down with single-function tilt operator for optimum light and privacy control
- Tilt Operator located in top right-hand corner
- Easy to maintain, simply clean with soap and water, or high quality window cleaner
- 10-year full warranty
- Blinds certified safe for children and pets with no exposed cords



SIZES	
IG Thickness	7/8"
Height Range	12" to 68"
Width Range	8" to 54"
Size Increments	1/16" (height & width)
Max IG size	Annealed glass: Up to 9 sq. ft. Tempered glass: Up to 9 sq. ft. (no more than 36" in one direction)

Please refer to charts located on the right for custom size options.

LOW-E OPTIONS	
Single	270, 272, 340 and 366
Dual	189/270, 189/272, 189/340, & 189/366


GLASS TINT	
Solar Gray	Solar Bronze

FINISH OPTIONS

Blind slats, operators, operator track and decorative cover caps are available in six different colors





CUSTOM SIZE OPTIONS





7/8" BLINDS + GLASS TILT FOR WINDOWS

TECHNICAL DRAWINGS & SPECIFICATIONS



OPERATION

Blind Function	Tilt
EasyGlide Operator	Clear Overmold/Two Shot
Single Operator	Annealed glass: Up to 9 sq. ft. Tempered glass: Up to 9 sq. ft.
Capillary Tube	Do not block, crush or cut
Operator Hand	Top Right

CODE OF COMPLIANCE

IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM C1036-16 (annealed) & C1048-12 (tempered)
ANSI (safety)	ANSI / WCMA A100.1-2018
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations

MATERIALS

Spacer	Intercept®, tin plated steel
Glass (Standard or Low-E)	1/8" annealed or 1/8" tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface hard coat Low-E (I89)
Glass Tint	Solar Gray or Solar Bronze: glass panel 1
Blind Slat	11.5mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer